

YUASA NP – NPL AKÜ ÖZELLİKLERİ

Yuasa NP (5 YIL ÖMÜR BEKLENTİLİ)

Model	Nominal Voltage	Nominal Capacity (Ah)		Dimensions			
	(V)	(20Hr)	(10Hr)	L (mm)	W (mm)	Height over Terminals (mm)	Weight Approx (Kg)
NP3-4	4	3.0	2.78	90.5	34	64	0.42
NP4.2-4H	4	4.4	4.20	48	35.5	119	0.56
NP10-4	4	10.0	9.25	102	50	98	1.35
NP1-6	6	1.0	0.93	51	42.5	54.5	0.25
NP1.2-6	6	1.2	1.11	97	25	54.5	0.31
NP2.8-6	6	2.8	2.60	134	34	64	0.57
NP3.6	6	3.0	2.78	134	34	64	0.63
NP4.2-6H	6	4.4	4.20	48	51.5	119	0.80
NP4-6	6	4.0	3.70	70	47	105.5	0.85
NP4-6W	6	4.0	3.70	70	47	102.5	0.85
NP7-6	6	7.0	6.48	151	34	97.5	1.32
NP10-6	6	10.0	9.25	151	50	97.5	1.93
NP12-6	6	12.0	11.10	151	50	97.5	2.05
NPL130-6	6	130.0	120.25	350	166	174	22.82
NP0.8-12	12	0.8	0.74	96	25	61.5	0.35
NP1.2-12	12	1.2	1.11	97	48	54.5	0.57
NPH1.3-12	12	-	1.30	97	48	54.4	0.64
NP2-12	12	2.0	1.85	150	20	89/85	0.70
NP2.1-12	12	2.1	1.90	178	34	64	0.83
NPH2-12FR	12	-	2.00	68	51	88	0.84
NP2.3-12	12	2.3	2.13	178	34	64	0.94
NP2.8-12	12	2.8	2.60	134	67	64	1.10
NP3.2-12	12	3.2	3.00	134	67	64	1.17
NPH3.2-12	12	-	3.20	134	67	64	1.40
NP4-12	12	4.0	3.70	90	70	106	1.57
NPH5-12	12	-	5.00	90	70	106	2.00
NP7-12	12	7.0	6.48	151	65	97.5	2.65
NP12-12	12	12.0	11.10	151	98	97.5	4.09
NP17-12	12	17.0	13.88	181	75	167	6.20
NPH16-12	12	-	16.00	181	76	167	6.20
NP24-12	12	24.0	22.20	166	175	125	8.92
NP38-12	12	38.0	35.15	197	165	170	13.93
NP65-12	12	65.0	60.13	350	166	174	22.82
NPL78-12	12	78.0	72.15	380	166	174	27.50

Yuasa NPL (10 YIL ÖMÜR BEKLENTİLİ)

	NPL130-6i	NPL24-12i	NPL38-12i	NPL65-12i	NPL78-12iFR
Nominal Capacity (Ah)					
20hr to 1.75vpc 20°C	130	24	38	65	78
10hr to 1.75vpc 20°C	120	22.3	35.3	60.5	72.6
5hr to 1.70vpc 20°C	110	20.4	32.3	55.3	66.3
1hr to 1.60vpc 20°C	78	14.4	22.8	39	46.8
Voltage	6	12	12	12	12
Energy Density (Wh/L)	77	79	83	77	85
Specific Energy (Wh.kg)	34	32	32	34	34
Int Resistance (m.ohms)	2.5	9.5	7.5	5	<5
Maximum discharge (A)	390	150	200	500	500
Short Circuit current (A)	800	500	500	800	800
Dimensions (mm)					
Length	350	166	197	350	380
Width	166	175	165	166	166
Height overall	174	125	170	174	174
Weight	23	9	14.2	23	27.5
Terminal	C	A	B	C	C/D
Torque Nm	4.76	2.45	2.45	4.76	4.76/6.1